

LED T8 3 Foot Linear Retrofit Tube Bulbs

Search Code: SC6843



FEATURES

- **Durable Construction:** Shock and vibration resistant.
- **Material:** Glass tube with white housing.
- **Customizable Settings:** Choose your wattage and color temperature. Available in 3000K Soft White, 3500K Neutral White, 4000K Cool White and 5000K Daylight.
- **Solid State LED lighting.**
- **Frosted lense.**
- **IP Rating:** IP20 damp location (Indoor).
- **Perfect for applications with frequent 'on/off' switching cycles.**
- **Tubes are made of glass and will require a sleeve for food service applications.**
- **Beam Angle:** 210°.
- **Base Type:** Medium Bi-Pin G13 Base.
- **Single sided and Double sided bypass available.**
- **Direct Replacement Option-** for use on **ELECTRONIC T8 BALLASTS ONLY - Instant Start and Rapid Start Ballasts.**
- **Available size:** 3 Foot.

ELECTRICAL

- **Voltage:** 120-277V.
- **CRI:** ≥ 80.
- **Power Factor:** 0.9.
- **Total Harmonic Distortion (THD):** < 20%.
- **Operating Temperature Range:** (-17°C to 45°C) 0°F to 113°F.
- **Frequency Range:** 50Hz~60Hz.



WARRANTY & LISTINGS

- **Warranty:** 5 years (50,000 operational hours).
- **Certifications:** cULus Listed, FCC Compliant, Canadian Standard ICES-005, NSF Approved, IP20 for damp locations, RoHS, DLC Listed.

INSTALLATION ⚠

Before Install Make Sure To:

- ✓ Read the included instructions regarding your method of installation.
- ✓ Please check compatibility of existing ballast when required.
- ✓ Turn off the power at the breaker.
- ✓ All work should be performed by a qualified electrician where needed.
- ✓ Always install one test lamp before proceeding with the full area.

APPLICATION

- **Commercial spaces:** Used in troffers and linear fixtures.
- **Warehouses:** Common in high bays and strip lighting.

ORDERING INFORMATION

Product Code	Type	Wattage	Lumens	Color Temperature
S49993	No Rewiring - T8 Ballast Compatible	10W	1400L	5000K Daylight
S49992	No Rewiring - T8 Ballast Compatible	10W	1400L	4000K Cool White
S49991	No Rewiring - T8 Ballast Compatible	10W	1400L	3500K Neutral White
S49990	No Rewiring - T8 Ballast Compatible	10W	1400L	3000K Soft White
T8-EZ6-GS-3FT-12W-50K-F	Universal - Bypass or Ballast Compatible	12W	1560L	5000K Daylight
T8-EZ6-GS-3FT-12W-40K-F	Universal - Bypass or Ballast Compatible	12W	1560L	4000K Cool White
S39929	Yes Rewiring - T8 Ballast To Be Bypassed	12W	1560L	5000K Daylight
S39928	Yes Rewiring - T8 Ballast To Be Bypassed	12W	1560L	4000K Cool White
S39927	Yes Rewiring - T8 Ballast To Be Bypassed	12W	1560L	3500K Neutral White
S39926	Yes Rewiring - T8 Ballast To Be Bypassed	12W	1560L	3000K Soft White

LED T8 3 Foot Linear Retrofit Tube Bulbs

Search Code: SC6843



DIMENSIONS


3 FOOT



DIAGRAMS

BALLAST REWIRING

Single Sided Bypass.



BALLAST REWIRING

Double Sided Bypass.

