

LED BULLET FLOOD LIGHTS



Certification



Features

- Housing: ADC 12 Aluminum heat sink, SUS back plate, outdoor powder coating
- Optical lens: High transmittance PC, anti-UV and fire resistant
- 60° beam angle
- CRI: >80
- Power Factor: >0.9
- LED: Philips LUMILEDs
- 130LM/W
- Voltage: 100~277V/ 50~60Hz
- Fully adjustable 1/2" NPT threaded knuckle
- Aluminum LED board: High conductive, waterproof, aging resistance, salt mist resistance
- 5-year warranty
- Suitable for wet locations, IP65

FLD2-15CW-KN
FLD2-15WW-KN



FLD2-15WW-TR
FLD2-15CW-TR



FLD2-28CW-KN
FLD2-28CW-KN



FLD2-28CW-TR
FLD2-28WW-TR



FLD2-42WW-KN
FLD2-42CW-TR



FLD2-42CW-TR
FLD2-42WW-TR



LED Bullet Flood Light Specifications

Product #	Watt	Mount	Lumens	Color Temp	Volt	Dimensions
FLD2-15CW-KN	15W	KNUCKLE	1500	5000K	120 / 277V	3"(W) x 5-1/2"(H) x 4-1/4"(D) 3" Diameter
FLD2-15WW-KN	15W	KNUCKLE	1500	3000K	120 / 277V	
FLD2-28CW-KN	28W	KNUCKLE	2800	5000K	120 / 277V	4"(W) x 7-1/2"(H) x 5-3/4"(D) 4" Diameter
FLD2-28CW-KN	28W	KNUCKLE	2800	3000K	120 / 277V	
FLD2-42WW-KN	42W	KNUCKLE	4200	5000K	120 / 277V	4-1/2"(W) x 8"(H) x 6-1/4"(D) 4-1/2" Diameter
FLD2-42CW-TR	42W	KNUCKLE	4200	3000K	120 / 277V	
FLD2-15WW-TR	15W	TRUNNION	1500	5000K	120 / 277V	3"(W) x 5"(H) x 4-1/4"(D) 3" Diameter
FLD2-15CW-TR	15W	TRUNNION	1500	3000K	120 / 277V	
FLD2-28CW-TR	28W	TRUNNION	2800	5000K	120 / 277V	4-1/2"(W) x 7-3/4"(H) x 5-3/4"(D) 4" Diameter
FLD2-28WW-TR	28W	TRUNNION	2800	3000K	120 / 277V	
FLD2-42CW-TR	42W	TRUNNION	4200	5000K	120 / 277V	4-1/2"(W) x 8-1/2"(H) x 6-1/4"(D) 4-1/2" Diameter
FLD2-42WW-TR	42W	TRUNNION	4200	3000K	120 / 277V	