

LED DUSK-TO-DAWN FIXTURE



Features
Performance
<ul style="list-style-type: none"> ● 76,000 Hours Of Maintenance-Free Operation To L₇₀ ● Operating Temperature Range -22° F - 104° F ● 5-Year Warranty
Construction & Materials
<ul style="list-style-type: none"> ● Durable Die-Cast Aluminum Housing. ● Grey Polyester Powder-Coat Finish For Extra Corrosion Protection. ● Polyester Powder-Coat Grey Finish For Extra Corrosion Protection. ● Mount Directly Or With Included Mounting Arm. ● Mounting Arm Diameter: 1.69"
Electrical
<ul style="list-style-type: none"> ● Non-Dimmable ● 120V Operation ● Twist-Lock Photocell Included
Regulatory
<ul style="list-style-type: none"> ● UL Listed For Wet Locations

Dimensions Include Mounting Arm



23"(L)x9"(W)x15.5"(H)



20"(L)x7 1/2"(W)x13"(H)



10.82"(L)x4.33"(W)x11"(H)

Specifications								
Product Code	Wattage	Lumens	Color Temp	Replaces	Input Voltage	LED Lifetime	Voltage	Housing Color
7101CAAL030	30Watt	3,000LM	5000K	100 Watt Metal Halide	120V	76,000 Hours	120V	Silver
7101CAAL045	45 Watt	4,900LM	5000K	175 Watt Metal Halide	120V	76,000 Hours	277V	Silver
7101CAAL068-Bronze	70 Watt	10,000LM	5000K	250 Watt Metal Halide	120V	76,000 Hours	277V	Bronze
7101CAAL068	70 Watt	10,000LM	5000K	250 Watt Metal Halide	120V	76,000 Hours	277V	Silver