LED Barn Light Dusk-To-Dawn With Photocell

Search Code: SC6275



STANDARD









FEATURES

- High Efficiency: CREE LEDs Up to 133 lm/W.
- Durable Construction: Polyester, aluminum, and metal housing with a shatter, shock, and vibration-resistant polycarbonate prismatic lens.
- Versatile Applications: Suitable for commercial and residential settings.
- Dimmable Options: 0-10v Smooth dimming.
- Customizable Settings: Available in multiple wattages and color temperatures. CCT switch is on the housing.
- Accessories: NEMA Twist-Lock photocell for dusk to dawn operation, extension arm, mounting bracket, and hardware.
- Wide Beam Angle: 120°
- IP Rating: Waterproof and dustproof (IP65 rated).
- Long Lifespan: Rated for up to 50,000 operational hours.

ELECTRICAL

- Voltage: 120V-277V Input Voltage.
- Efficacy: Up to 133 lm/W.
- Power Factor: > 0.9.
- CRI:>80.
- Total Harmonic Distortion (THD): < 20%.
- Operating Temperature Range: -17°C 40°C (0°F -104°F).
- Power Source: Hardwired-Electric.

APPLICATION

- Residential Perimeters
- Parking Lots
- Commercial Buildings
- Pathways
- Warehouses
- Barns
- Sheds



WARRANTY & LISTINGS

- Warranty: 5 years (50,000 operational hours).
- Certifications: cULus Listed, DLC Listed.

MOUNTING OPTIONS

- Direct wall mount.
- Arm mount for poles.

CCT CONFIGURATION

Remove cap to access color and watt selector switches



Wattage Select







Photocell





Sensor ON

Sensor OFF

Color Select







ORDERING INFORMATION


Product Code	Wattage	Lumens	Color Temperature	Mounting Height
DTD-45W-7FCCT-UD-PC	45W	6,200L	Color Select 30K/40K/50K	12-14 Feet
7101CAAL070	70W	10,000L	5000K Daylight	15-18 Feet
DTD-80W-7FCCT-UD-PC	80W	11,100L	Color Select 30K/40K/50K	18-20 Feet
DTD-120W-7FCCT-UD-PC	120W	16,000L	Color Select 30K/40K/50K	20-25 Feet
7101CAAL150-K	150W	20,000L	5000K Daylight	25-30 Feet

LED Barn Light Dusk-To-Dawn With Photocell


Search Code: SC6275




45W



70W



80W & 120W



150W

23.84"

