

LED HI-OUTPUT POST TOP RETROFIT BULBS



Certification



Applications / Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures and cULus listed
- Damp location - IP65 rated For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)



LED Hi-Output Post Top Retrofit Bulbs Specifications

Product Code	Color Temperature Option	Watt	Lumens	Base	Volts	Dimensions
S9678	Amber	18		Medium E26	100-277	6-7/8" x 2-3/4"
S9670	2700K Warm White	18	2200	Medium E26	100-277	6-7/8" x 2-3/4"
CB-20-50K-E26	5000K Daylight	20	2400	Medium E26	100-277	7-3/32" x 3-9/16"
S9671	2700K Warm White	22	2680	Medium E26	100-277	7-11/16" x 2-3/4"
CB-35-50K-E39	5000K Daylight	30	4300	Mogul E39	100-277	8-11/16" x 3-9/16"
CB-35-50K-E26	5000K Daylight	30	4300	Medium E26	100-277	8-11/16" x 3-9/16"
S9672	2700K Warm White	36	4390	Medium E26	100-277	9-1/4" x 3.69"
S9673	4000K Cool White	45	5850	Mogul E39	100-277	10-3/4" x 3.69"
CB-45-50K-E39	5000K Daylight	54	6000	Mogul E39	100-277	10-3/4" x 3.69"
S9674	4000K Cool White	54	7020	Mogul E39	100-277	10-3/4" x 3.69"

Product Code	Color Temperature Option	Watt	Lumens	Base	Volts	Dimensions
CB-54-50K-E39	5000K Daylight	54	6480	Mogul E39	100-277	10-3/4" x 3.69"
S9675	4000K Cool White	80	10400	Mogul E39	100-277	9-1/4" x 5.87"
CB-80-50K-E39	5000K Daylight	80	10640	Mogul E39	100-277	9-1/4" x 5.87"
S9676	4000K Cool White	100	13000	Mogul E39	100-277	9-5/8" x 5.87"
CB-100-50K-E39	5000K Daylight	100	12000	Mogul E39	100-277	11.26" x 5-3/4"
S9677	4000K Cool White	120	15600	Mogul E39	100-277	10-3/8" x 5-7/8"
CB-120-50K-E39	5000K Daylight	120	14400	Mogul E39	100-277	12" x 5-3/4"
CB-120-50K-E39	5000K Daylight	120	14400	Mogul E39	100-277	12" x 5-3/4"
CB-140-50K-E39	5000K Daylight	140	16880	Mogul E39	100-277	13.3" x 4.75"