

LED Dimmable Recessed Retrofits



Certifications



Specifications

- Voltage: 120V
- Life Hours: 35,000
- CRI: 82
- Input Line Frequency: 50/60Hz
- Minimum Start Temperature: -20 degrees C
- Maximum Start Temperature: 40 degrees C
- Energy Star Rated: Yes
- Dimmable
- Instant ON to full brightness
- 100% direct replacement
- UL Listed
- 5-year warranty
- UL approved for damp locations

Application

- Perfect for retrofit or new construction recessed downlight applications



| | | |
|---------------|----------|------|
| Length | L | 5" |
| Height | H | 3.8" |



| | | |
|---------------|----------|------|
| Length | L | 7.5" |
| Height | H | 3.8" |

Specifications

| Product # | Watts | Lumens | Color Temp | Hours |
|------------------|-------|---------|------------------|--------------|
| S9312 | 9W | 650 LM | 2700K Warm White | 35,000 Hours |
| S9314 | 9W | 650 LM | 4000K Cool White | 35,000 Hours |
| S9315 | 9W | 650 LM | 5000K Daylight | 35,000 Hours |
| LED14DR5627K-TCP | 14W | 1250LM | 2700K Warm White | 35,000 Hours |
| LED14DR5630K-TCP | 14W | 1250 LM | 3000K Soft White | 35,000 Hours |
| LED14DR5641K-TCP | 14W | 1250 LM | 4000K Cool White | 35,000 Hours |
| LED14DR5650K-TCP | 14W | 1250 LM | 5000K Daylight | 35,000 Hours |
| LED10DR427K-TCP | 10W | 700 LM | 2700K Warm White | 35,000 Hours |
| LED10DR430K-TCP | 10W | 700 LM | 3000K Soft White | 35,000 Hours |
| LED10DR440K-TCP | 10W | 700 LM | 4000K Cool White | 35,000 Hours |