

# Commercial LED Decorative Post Top Light

Search Code: SC10526



## FEATURES

- *Durable Construction: Aluminum housing with polycarbonate optics lens.*
- *Optics: Frosted Tempered Glass.*
- *Clean classic design with a black finish.*
- *Dimmable Options: Standard 0-10v smooth dimming compatibility.*
- *Versatile Applications: Compatible with commercial and residential settings.*
- *Customizable Settings: Available in multiple wattages and color temperatures. Color temperature is adjustable inside fixture, select between 3000K Soft White, 4000K Cool White, and 5000K Daylight.*
- *Wide Beam Angle: 270°.*
- *IP Rating: Wet Rated.*
- *Long Lifespan: Rated for up to 50,000 operational hours.*

## ELECTRICAL

- *Voltage: 120V-277V.*
- *CRI: >70.*
- *Power Factor: >0.95.*
- *Total Harmonic Distortion (THD): 18.17%.*
- *Operating Temperature Range: -17°C to 50°C ( 0°F to 122°F ).*
- *Frequency Range: 50Hz~60Hz.*

## APPLICATIONS

- *Courtyards.*
- *Public Parks.*
- *Hotels.*
- *Parking Areas.*



## WARRANTY & LISTINGS

- *Warranty: 5 years (50,000 operational hours).*
- *Certifications: ETL Listed, Wet location Rated, DLC Compliant.*

## MOUNTING

- *Easy installation in new construction or retrofit applications. Fits on a 3" pole.*

## DIMENSIONS



## ORDERING INFORMATION

Product Code	Wattage	Lumens	Color Temperature	Accessories
7614CLBL030-MCT-LED	30W	3600L	Selectable 3K/4K/5K	As-Is None
7614CLBL030-MCT-LEDP	30W	3600L	Selectable 3K/4K/5K	Photocell
7614CLBL060-MCT-LED	60W	7200L	Selectable 3K/4K/5K	As-Is None
7614CLBL060-MCT-LEDP	60W	7200L	Selectable 3K/4K/5K	Photocell