



18, 22, 35, 45, 54, 80, 100, 120 Watts Available



Item #	Lamp Code	Watts	Replaces INC / CFL / HID	Input Voltage	Base Type	CCT	Lumens	Dimensions
S9390	18W/LED/HID/5000K/100-277V	18W	120 / 32 / 70	100-277	E26	5000K	2160	67/8" x 23/4"
S9391	22W/LED/HID/5000K/100-277V	22W	150 / 40 / 100	100-277	E26	5000K	2640	711/16" x 23/4"
S9392	36W/LED/HID/5000K/100-277V	36W	200 / 55 / 150	100-277	E26	5000K	4320	91/4" x 3.69"
S9393	45W/LED/HID/5000K/100-277V	45W	300 / 65 / 175	100-277	E39	5000K	5400	103/4" x 3.69"
S9394	54W/LED/HID/5000K/100-277V	54W	300 / 85 / 250	100-277	E39	5000K	6480	103/4" x 3.69"
S9395	80W/LED/HID/5000K/100-277V	80W	400 / 100 / 320	100-277	E39	5000K	9600	91/4" x 5.87"
S9396	100W/LED/HID/5000K/100-277V	100W	500 / 150 / 400	100-277	E39	5000K	12000	95/8" x 5.87"
S9397	120W/LED/HID/5000K/100-277V	120W	750 / 200 / 600	100-277	E39	5000K	14400	103/8" x 5.87"

Average Rated Hours	Base	Color	CRI	Dimmable Non Dimmable	Finish	Pack	Package Type	ROHS Compliant	UL or ETL Listed
50,000 Hours	E26 or E39	Daylight	80+	Non-Dimmable	White	48	Box	Yes	Yes

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Min Starting Temp -20°C
- Max Starting Temp 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Optional accessory: In-line surge protector [80-929](#)