

LED Recessed Can Downlights

Search Code: SC10983



STANDARD



FEATURES

- **High Efficiency:** Up to 85 lm/W
- **Durable Construction:** Aluminum construction. White powder coat finish with a 0.125" White translucent acrylic glare free lens and a Isolated driver for improved thermal management.
- **Versatile Applications:** Suitable for residential and commercial settings.
- **Dimmable Options:** TRIAC smooth dimming compatibility with using standard TRIAC LED dimmers.
- **Customizable Settings:** Available in multiple wattages and color temperatures. Color temperature is adjustable on select models.
- **Two Sizes:** 4 or 6 inch options.
- **IP Rating:** IP20 damp location. Airtight standards conformance, Class A sound rating.
- **Environmentally friendly** - contains no mercury or other hazardous materials. 80% more efficiency than most halogen or incandescent lamps.
- **Quick and easy installation.**
- **Long Lifespan:** Rated for up to 35,000 operational hours.

ELECTRICAL

- **Voltage:** 120V AC.
- **Output Voltage:** 36VDC.
- **CRI:** >80.
- **Power Factor:** > 0.90.
- **Total Harmonic Distortion (THD):** ≤ 15%.
- **Operating Temperature Range:** (-17°C to 40°C) 0°F to 104°F.



WARRANTY & LISTINGS

- **Warranty:** 3 years (35,000 operational hours).
- **Certifications:** Energy Star Rated, UL Listed, cULus Listed for damp locations and insulated ceilings.
- **Compliance:** RoHS and FCC compliant.

MOUNTING

- **Standard ceiling recessed mounting.**


ACCESSORIES

- **E26 medium base adapter included.**

APPLICATION

- **Kitchen.**
- **Living Rooms.**
- **Bedrooms.**
- **Office Spaces.**

DIMENSIONS



ORDERING INFORMATION

Product Code	Size	Wattage	Lumens	Color Temperature
S11800	4"(D)	7W	600L	Color Select 27K,30K,35K,40K,50K
RDPS6-MCT5	6"(D)	11W	1000L	Color Select 27K,30K,35K,40K,50K
L75DR56D3527K	6"(D)	11W	1000L	2700K Warm White
RDL6-27K-WP	6"(D)	15W	1275L	2700K Warm White
RDL6-ST-MCT5	6"(D)	15W	1275L	Color Select 27K,30K,35K,40K,50K
RDL6-30K-WP	6"(D)	15W	1275L	3000K Soft White
RDL6-41K-WP	6"(D)	15W	1275L	4000K Cool White
RDL6-50K-WP	6"(D)	15W	1275L	5000K Daylight
RDR6-120-17W-830-120DT-WH-B	6"(D)	17W	1200L	3000K Soft White