

LED Turtle Friendly WallPack

Search Code: SC65579



FEATURES

- **Durable Construction:** Die-cast aluminum housing with a black or white powder coat Finish.
- **Lens:** High-Transmission polycarbonate lens.
- **Surge Protection:** Built-in surge protection - 2.5KV.
- **Dimming:** (Dual Function) Triac Dimmable at 120V & 0-10V Dimming at 120-277V.
- **Multi CCT:** 4000K Cool White and Warm Amber.
- **Versatile Applications:** Suitable for residential and commercial settings.
- **Wet Location Rated.**
- **Long Lifespan:** Rated for up to 50,000 operational hours.

ELECTRICAL

- **Input Voltage:** 120-277V.
- **CRI:** 80+.
- **Operating Temperature Range:** (-17°C to 40°C) 0°F to 113°F.

APPLICATION

- Beachfront properties.
- Coastal walkways.
- Oceanfront resorts or hotels.
- State parks near marine environments.
- Boardwalks.
- Boat ramps.
- Park restroom or utility structures near shorelines.



WARRANTY & LISTINGS

- **Warranty:** 5 years. 50,000 operational hours.
- **Certifications:** RoHS Compliant, FCC Compliant, IP65 Wet Rated, Turtle Safe.

ACCESSORIES INCLUDED

- Photocell.

DIMENSIONS



ORDERING INFORMATION

Product Code	Wattage	Finish	Lumens	Color Temperature
65-888	20W	Black	2493L	Selectable 4000K / Amber
65-889	20W	White	2493L	Selectable 4000K / Amber