

LED SLIM SQUARE RECESSED LIGHTS



Certifications



Specifications

- Die-cast aluminum with white powdercoat finish
- Pot light housing is not required even for insulated ceilings
- Optics: White translucent acrylic lens
- Lens: 0.125" white translucent acrylic
- Type IC rated-Approved for direct contact with insulation
- CRI: >80
- Working voltage: 120V AC
- Beam Spread: 100-110°
- Dimmable
- LED: Seoul DOB (Driver On Board) Technology
- Power Factor: 90% +
- Air-tight and damp location approved
- Maximum Ambient Temperature: -40°F~104°F
- Rated Life: 50,000 hrs, 5-year warranty
- ETL-listed
- Energy Star-rated

Specifications

Product #	Watts	Lumens	Color Temp	Size
SSL4-27K	9W	540 LM	2700K Warm White	4"
SSL4-30K	9W	540 LM	3000K Soft White	4"
SSL4-40K	9W	540 LM	4000K Cool White	4"
SSL4-50K	9W	540 LM	5000K Daylight	4"
SSL6-27K	15W	900 LM	2700K Warm White	6"
SSL6-30K	15W	900 LM	3000K Soft White	6"
SSL6-40K	15W	900 LM	4000K Cool White	6"
SSL6-50K	15W	900 LM	5000K Daylight	6"